



Scottoiler: Honda XR600R XR400 XR250 Scottoiler eSystem (the electronic Scottoiler) Installation Guide



The Dispenser assembly can be secured on the chain guard bolt using the small dispenser plate and clip. The delivery tubing can be routed along the swing arm using conduit and glue or self adhesive cable clips. See our easy step installation guide [Dispenser Assemblies, General](#). The nib should feed the rear sprocket between 6 and 7 o'clock with the slash cut facing outwards.

Connect the delivery tubing to the check valve but do not connect the check valve, part 6, to the REP, part 7, until you are priming the system.

See picture below left



The REP can be mounted on the fork leg and can be orientated anywhere between horizontal and vertical, as long as the nozzle is inclined upwards. Remember to avoid exhaust and engine components and to keep the filling hole accessible. For further information, see our easy step installation guide – [Reservoir Positions, General](#).

See third picture

Note: Picture shows a similar Swingarm



The Display Bracket, part 5, can be rotated through 360° to give 4 mounting options and can also be flipped to provide 4 further options. The bracket can be secured to any M5 / M6 bolt e.g. brake or clutch lever, brake cylinder or fairing mountings, in some cases you might need to trim the supplied bolt. It is possible to bend the bracket to shape, do so before fitting the Display Unit, part 1, to prevent damage to the unit. Alternatively, the Sticky Fastener, part 4, can be used to securely fasten the Display Unit to any flat surface e.g. the fork yokes.

See picture bottom left

Note: Picture shows a similar reservoir



Locate the bikes' battery and attach the red terminal from the display unit to the +ve terminal on the battery, and attach the black terminal to the -ve terminal of the battery. Take care when routing the wires, avoiding hot engine and exhaust components also avoiding moving parts such as the throttle linkages. Where possible follow existing wiring and secure using cable ties.

Once fitted, fill the REP and prime the pump, then connect the check valve to the REP and prime the delivery tubing following the instructions supplied with the kit. For further information, see the website [eSystem page](#) which includes the Setup and Installation Guide. Set the flow rate using the 'Driving Screen' on the Display Unit to 60-70 seconds per drop (s/dp), check the condition of your chain after a ride, and then adjust as required.

Note: This is a generic image

If you have any further comments or queries, and are unable to resolve them using our website, please do not hesitate to call technical on 0141 955 1100 or email technical@scottoiler.com for assistance. Thank you.

Scottoiler Ltd. 2 Riverside, Milngavie, Glasgow, G62 6PL Tel. 0141 955 1100 Fax. 0141 956 5896 www.scottoiler.com

